

Product Specifications

Category	Product	Sweep (mm)	Power (W)	Input AC Voltage (V)	RPM	Air Delivery CMM (m3/min)	Power Factor	Service Value (CMM/W) (CMH)	Energy Savings
Ceiling	Renesa Smart +	1200	28	140-285	340	220	0.99	7.9	65%
	Studio+	1200	32	140-285	370	237	0.99	7.4	57%
	Renesa+	900	28	140-285	525	210	0.98	7.5	65%
		1200	28	140-285	340	220	0.99	7.9	65%
		1400	32	140-285	250	270	0.99	8.4	65%
	Renesa	600	28	140-285	830	135	0.99	4.8	65%
		1200	28	140-285	340	230	0.99	8.2	65%
		1400	32	140-285	250	270	0.99	8.4	65%
	Efficio	900	28	140-285	470	157	0.99	5.6	65%
		1050	32	140-285	400	235	0.99	7.3	65%
		1200	28	140-285	350	230	0.99	8.2	65%
		1400	35	140-285	250	270	0.99	7.7	65%
	Renesa Alpha	1200	32	140-285	320	241	0.9	7.5	60%
	Efficio +	900	28	140-285	470	157	0.99	5.6	65%
		1200	28	140-285	350	230	0.99	8.2	65%
1400		35	140-285	250	270	0.99	7.7	65%	
Ozeo	1200	28	140-285	340	235	0.99	8.3	65%	
Studio	1200	32	140-285	300	235	0.99	7.3	65%	
Exhaust	Studio+	150	7.5	140-285	2250	-	-	250	62%
	Studio	150	6.5	140-285	2000	-	-	245	72%
	Efficio+	150	5	220-240	1400	-	-	245	80%
	Efficio	150	11	140-285	2000	-	-	356	56%
		200	16	140-285	1600	-	-	800	56%
		250	20	140-285	1300	-	-	1150	56%
Pedestal Wall	Efficio+ Pedestal	400	32	90-245	1350	88	-	2.8	42%
	Efficio+ Wall	400	32	90-245	1350	71	-	2.06	42%

Atomberg Technologies Pvt Ltd

1205, Millennium Business Park, MIDC Industrial Area,
 Sector 1, Kopar Khairane, Navi Mumbai ,Maharashtra- 400 710
 Office : 844-844-9442
 Email : support@atomberg.com